



SAFETY DATA SHEET
Thick Tile & Vinyl - 026A

Product Name: Thick Tile & Vinyl
Date: 5/19/2015

SECTION 1 **IDENTIFICATION**

Supplier: Phoenix Products Company
55 Container Drive
Terryville, CT 06786
(860) 589-7502

Distributor:

U.S. PERS Emergency Telephone: 1-800-633-8253

Product Name: Thick Tile & Vinyl

Synonyms: None

Chemical Name: Not Available

Chemical Formula: Not Available

CAS Number: Not Available

Product Use: Removes body oils, chemical residues, lotions and dirt that create film at the tile line.

SECTION 2 **HAZARDS IDENTIFICATION**

EMERGENCY OVERVIEW

OSHA Regulatory Status: This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.122). Not a dangerous substance or mixture according to the Globally Harmonized System (GHS).

Potential Acute Health Effects: Slightly hazardous in case of skin contact (irritant, permeator), of eye contact (irritant), of ingestion, of inhalation.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available.

MUTAGENIC EFFECTS: Not available.

TERATOGENIC EFFECTS: Not available.

DEVELOPMENTAL TOXICITY: Not available. The substance may be toxic to kidneys. Repeated or prolonged exposure to the substance can produce target organs damage.

SECTION 3 **COMPOSITION, INFORMATION ON INGREDIENTS**

Component	CAS Number	Percent
Ultimate Clean	Not Available	39%
Glycerine	56-81-5	1%

SECTION 4 **FIRST-AID MEASURES**

Eye Contact: Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops. Cold water may be used.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.



SAFETY DATA SHEET
Thick Tile & Vinyl - 026A

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.

SECTION 5 **FIRE FIGHTING MEASURES**

Flammability of the Product: May be combustible at high temperature.

Auto-Ignition Temperature: 370°C (698°F)(NFPA Fire Protection Guide to Hazardous Materials, 13th ed., 2002; NIOSH ICSC, 2001; CHRIS, 2001) 392 C (739 F) (Lewis, 1997)

Flash Points: CLOSED CUP: 160°C (320°F). (Chemical Hazard Response Information System, 2001; Lewis, 1997). **OPEN CUP:** 177°C (350.6°F) (Budavari, 2000; Chemical Response Information System, 2001; NIOSH ICSC, 2001) **OPEN CUP:** 199 C(390 F) (National Fire Protection Association, Fire Protection Guide to Hazardous Materials, 13 ed., 2002)

Flammable Limits: LOWER: 0.9%

Products of Combustion: These products are carbon oxides (CO, CO₂), irritating and toxic fumes.

Fire Hazards in Presence of Various Substances: Slightly flammable to flammable in presence of open flames and sparks, of heat, of oxidizing materials. Non-flammable in presence of shocks.

Explosion Hazards in Presence of Various Substances: Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available. Explosive in presence of oxidizing materials.

Fire Fighting Media and Instructions: SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards: Glycerine is incompatible with strong oxidizers such as chromium trioxide, potassium chlorate, or potassium permanganate and may explode on contact with these compounds. Explosive glyceryl nitrate is formed from a mixture of glycerin and nitric and sulfuric acids. Perchloric acid, lead oxide + glycerine form perchloric esters which may be explosive. Glycerine and chlorine may explode if heated and confined.

SECTION 6 **ACCIDENTAL RELEASE MEASURES**

Small Spill: Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Large Spill: Stop leak if without risk. If the product is in its solid form: Use a shovel to put the material into a convenient waste disposal container. If the product is in its liquid form: Do not get water inside container. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Call for assistance on disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the SDS and with local authorities.

SECTION 7 **HANDLING AND STORAGE**

Precautions: Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. If



SAFETY DATA SHEET
Thick Tile & Vinyl - 026A

ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area. Hygroscopic

SECTION 8 **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the workstation location.

Personal Protection: Safety glasses. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill: Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: TWA: 10 (mg/m³) from ACGIH (TLV) [United States] [1999] Inhalation Total.
TWA: 15 (mg/m³) from OSHA (PEL) [United States] Inhalation Total.
TWA: 10 STEL: 20 (mg/m³) [Canada]
TWA: 5 (mg/m³) from OSHA (PEL) [United States] Inhalation Respirable. Consult local authorities for acceptable exposure limits.

SECTION 9 **PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Colorless Viscous Liquid
Odor:	Mild
Odor Threshold:	Not available.
pH (1% Solution/Water):	Not available.
Boiling Point/Boiling Range:	290°C (554°F)
Melting Point/Freezing Point:	19°C (66.2°F)
Critical Temperature:	Not available.
Specific Gravity:	1.2636 (Water = 1)
Vapor Pressure:	0 kPa (@ 20°C)
Vapor Density:	3.17 (Air = 1)
Volatility:	Not available.
Water/Oil Dist. Coeff:	The product is more soluble in water; log(oil/water) = -1.8
Ionicity (in Water):	Not available.
Dispersion Properties:	See solubility in water, acetone.

Solubility: Miscible in cold water, hot water and alcohol. Partially soluble in acetone. Very slightly soluble in diethyl ether (ethyl ether). Limited solubility in ethyl acetate. Insoluble in carbon tetrachloride, benzene, chloroform, petroleum ethers, and oils

SECTION 10 **STABILITY AND REACTIVITY**

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Avoid contact with incompatible materials, excess heat and ignition, sources, moisture.

Incompatibility with various substances: Highly reactive with oxidizing agents.

Corrosivity: Non-corrosive in presence of glass.



SAFETY DATA SHEET
Thick Tile & Vinyl - 026A

Special Remarks on Reactivity: Hygroscopic. Glycerine is incompatible with strong oxidizers such as chromium trioxide, potassium chlorate, or potassium permanganate. Glycerine may react violently with acetic anhydride, aniline and nitrobenzene, chromic oxide, lead oxide and fluorine, phosphorous triiodide, ethylene oxide and heat, silver perchlorate, sodium peroxide, sodium hydride.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

SECTION 11 **TOXICOLOGICAL INFORMATION**

Routes of Entry: Absorbed through skin. Eye contact.

Toxicity to Animals: WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 4090 mg/kg [Mouse]. Acute dermal toxicity (LD50): 10000 mg/kg [Rabbit]. Acute toxicity of the mist (LC50): >570 mg/m³ 1 hours [Rat].

Chronic Effects on Humans: May cause damage to the following organs: kidneys.

Other Toxic Effects on Humans: Slightly hazardous in case of skin contact (irritant), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals:

TDL (rat) - Route: Oral; Dose: 100 mg/kg 1 day prior to mating.

TDL (human) - Route: Oral; Dose: 1428 mg/kg

Special Remarks on Chronic Effects on Humans: Glycerine is transferred across the placenta in small amounts. May cause adverse reproductive effects based on animal data (Paternal Effects (Rat): Spermatogenesis (including genetic material, sperm morphology, motility, and count), Testes, epididymis, sperm duct). May affect genetic material.

Special Remarks on other Toxic Effects on Humans: Acute Potential Health Effects: Low hazard for normal industrial handling or normal workplace conditions. Skin: May cause skin irritation. May be absorbed through skin Eyes: May cause eye irritation with stinging, redness, burning sensation, and tearing, but no eye injury. Ingestion: Low hazard. Low toxicity except with very large doses. When large doses are ingested, it can cause gastrointestinal tract irritation with thirst (dehydration), nausea or vomiting diarrhea. It may also affect behavior/central nervous system/nervous system (central nervous system depression, general anesthetic, headache, dizziness, confusion, insomnia, toxic psychosis, muscle weakness, paralysisconvulsions), urinary system/kidneys (renal failure, hemoglobinuria), cardiovascular system (cardiac arrhythmias), liver. It may also cause elevated blood sugar. Inhalation: Due to low vapor pressure, inhalation of the vapors at room temperature is unlikely. Inhalation of mist may cause respiratory tract irritation. Chronic Potential Health Effects: Ingestion: Prolonged or repeated ingestion may affect the blood(hemolysis, changes in white blood cell count), endocrine system (changes in adrenal weight), respiratory system, and may cause kidney injury.

SECTION 12 **ECOLOGICAL INFORMATION**

Ecotoxicity: Ecotoxicity in water (LC50): 58.5 ppm 96 hours [Trout].

BOD5 and COD: Not available.

Products of Biodegradation: Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.



SAFETY DATA SHEET
Thick Tile & Vinyl - 026A

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

SECTION 13 *DISPOSAL CONSIDERATIONS*

Waste Disposal: Waste must be disposed of in accordance with federal, state and local environmental control regulations.

SECTION 14 *TRANSPORTATION DATA*

DOT: Not Regulated
TDG: Not Regulated
MEX: Not Regulated
IATA: Not Regulated

SECTION 15 *REGULATORY INFORMATION*

Federal and State Regulations: Illinois toxic substances disclosure to employee act: Glycerine
Rhode Island RTK hazardous substances: Glycerine
Pennsylvania RTK: Glycerine
Minnesota: Glycerine
Massachusetts RTK: Glycerine
Tennessee - Hazardous Right to Know: Glycerine
TSCA 8(b) inventory: Glycerine

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications

WHMIS (Canada): Not controlled under WHMIS (Canada).
DSCL (EEC): Not available S24/25- Avoid contact with skin and eyes.
HMIS (U.S.A.): Health Hazard: 1
Fire Hazard: 1
Reactivity: 0
Personal Protection: g

NFPA (U.S.A.): Health: 1
Flammability: 1
Reactivity: 0
Specific hazard:

SECTION 16 *ADDITIONAL INFORMATION*

No representations or warranties, either expressed or implied, of merchant ability, fitness for a particular purpose or any other nature are made hereunder with respect to information or the product to which information refers.



SAFETY DATA SHEET
Thick Tile & Vinyl - 026A

Date: 5/19/2015
Phoenix Products Company